

# AN/PVS-14 BRIDGE

## BINOCULAR BRIDGE SYSTEM



COLORS: ■ -B  
(BLACK)



AVAILABLE IN DOVETAIL  
OR HORN INTERFACE

### PRODUCT OVERVIEW

The AN/PVS-14 binocular bridge provides versatility allowing the end user to wear a PVS-14 as a monocular or add a second PVS-14 or a thermal for binocular needs. Offered in a dovetail shoe or horn interface, the PVS-14 binocular bridge fits securely into our G24 or G11 mount allowing the binocular configuration to be positioned into operational, high ready and stowed positions – the same as in a monocular configuration.

### NVG/THERMAL COMPATIBILITY

- AN/PVS-14
- SKEETIRx
- IR PATROL

*\*Other NVG/THERMAL devices are compatible but require additional accessories. Please call customer service for more information.*

### SPECIFICATIONS

DIMENSIONS:  
WEIGHT:  
INTERFACE:

4.5" L x 1.3" W x 2.1" H  
7.37 OZ  
DOVETAIL OR HORN

### FEATURES & BENEFITS

- Binocular or monocular configurable
- Available in Dovetail or Horn interface for use with different mounts
- Allows NVGs to be folded completely flat when stowed
- Several points of adjustment ensure proper eye relief
- Modular interface allows for quick removal
- Backed by Wilcox's lifetime warranty

### PART / NSN NUMBERS

PART NUMBER	DESCRIPTION	NSN NUMBER
61300G16	AN/PVS-14 BRIDGE	
61301G02	HORN INTERFACE	

AVAILABLE THROUGH:



FLE CO., LTD. 801 Route Nishiikebukuro Bldg. 5-17-11  
Nishiikebukuro Toshima-ku Tokyo 171-0021 Japan  
+81-3-5926-9940

